

# Dyna-Thread®

## Full Line Schedule 40 Replacement

- Widely accepted substitute for Schedule 40
- Standard hanger spacing
- UL and cUL listed
- FM approved

➤ **Combining the safety and longevity of Sch-40 with quality and hydraulic advantages.**

Dyna-Thread® pipe is the full line Schedule 40 replacement with the same CRR of Schedule 40, 1.00, providing Dyna-Thread with the same life expectancy as Sch-40. With outstanding hydraulic capabilities, Dyna-Thread is a more widely accepted product substitution than lightwall threadable pipe when Sch-40 is specified.

Dyna-Thread's inside diameter is up to 3.6% larger than Sch-40 and provides improved hydraulics. When used in combination with Dyna-Flow pipe, down sizing of pipe and related components often occurs, thereby reducing costs.

The consistent quality of steel used to make Dyna-Thread facilitates smooth threading and lower maintenance costs. Increased strength and lighter weight allows Dyna-Thread to reduce installation fatigue and makes it ideal for retro-fit applications.

Dyna-Thread Specifications					
NPS	Nominal I.D.	Wt.	Wt. (H2O Filled)	CRR	CRR
In; mm	In; mm	Lbs/Ft; kg/m	Lbs/Ft; kg/m	Unthreaded	Threaded
1"	1.080	1.330	1.75	11.39	1.00
25	27.4	2.0	2.60	—	—
1¼"	1.408	1.870	2.54	9.50	1.00
32	35.8	2.8	3.78	—	—
1½"	1.639	2.290	3.22	9.14	1.00
40	41.6	3.4	4.79	—	—
2"	2.104	3.050	4.57	8.41	1.00
50	53.4	4.5	6.80	—	—



➤ **Superior Coating**

Dyna-Thread products are coated with an environmentally approved and specially formulated modified-acrylic or water-based coating. This durable coating is paintable and acts as an excellent primer while resisting weather and UV degradation from outdoor storage.

➤ **American Made**

Able to meet "Buy American" requirements, and is available through distributors in the USA, Canada, Mexico and Latin America.

➤ **Specifications & Approvals**

Dyna-Thread pipe is manufactured to meet ASTM A-135, Type E Grade A, is in compliance with NFPA-13 and all sizes are rated at 300 psi working pressure. Dyna-

Thread is UL and cUL listed for wet, dry deluge and pre-action sprinkler systems and FM approved for use in wet systems. Dyna-Thread can be hot dip galvanized\*\* to meet FM requirements for use in dry systems. Dyna-Thread is approved for all threaded couplings and welded outlets and is suitable for all roll-grooved and plain end fittings.

\*\* must be ordered in 10 bundle increments



Customer Service (800) 882-5543 Fax: (800) 659-7730

• 16100 S Lathrop Ave.  
Harvey, IL 60426

• 11350 Norcom Rd.  
Philadelphia, PA 19154

• 2525 N 27th Ave.  
Phoenix, AZ 85009

• 600 Dean Sievers Place  
Morrisville, PA 19067

[www.alliedtube-sprinkler.com](http://www.alliedtube-sprinkler.com)