

XL®/BLT®

Submittal Data Sheet

Galvanized and Black Lightwall Threadable Pipe

XL/BLT's proven hydraulic advantage and lighter weight adds value to any system. When you need a proven sprinkler pipe, specify XL/BLT.

Product Description XL/BLT pipe is exceptionally strong steel sprinkler pipe of the class generally known as "lightwall threadable pipe". Its wall thickness is less than that of Sch-40 or Sch-10, but the cold forming process undergone in manufacturing gives XL/BLT pipe mechanical strength characteristics equivalent to those required for Sch-40. It is designed for use in wet, dry, pre-action and deluge systems. XL/BLT can be joined with threaded couplings (when in accordance with ANSI B1.20.1), roll grooved or plain-end couplings, or welded joints.

Other Benefits The clean surface quality of XL/BLT is readily paintable. The lighter weight of XL/BLT is a distinct advantage for retro-fit installations and can also reduce labor costs.

Coatings & Fabrication XL/BLT products have metallurgical properties which provide excellent fabrication characteristics for end prep finishes, welding and roll grooving. No special processes or equipment are needed for fabrication and installation. XL is manufactured with a galvanized exterior coating and BLT is black lacquer coated.

Superior Hydraulics XL/BLT pipe offers the maximum hydraulic advantage of any available threadable sprinkler pipe. Its inside diameter is up to 5% larger than Sch-40. The use of XL/BLT in conjunction with Dyna-Flow pipe, can dramatically improve the flow characteristics, thereby increasing the potential for "downsizing" system components.

American Made Able to meet "Buy American" requirements, and is available through distributors in the USA, Canada, Mexico and Latin America.

Specifications & Approvals XL/BLT pipe is manufactured to meet ASTM A135, Type E Grade A for fire sprinkler applications up to 300 psi working pressure. It is UL listed for wet, dry, pre-action and deluge systems, and FM approved for wet sprinkler systems. XL/BLT is ULC listed for wet, dry and pre-action systems. All threaded and welded fittings are approved in accordance with NFPA 13. FM requires 12' maximum hanger spacing for XL/BLT. C-Factors for XL/BLT are 120 for wet systems, and C=100 for dry systems. Refer to Hazen-Williams charts for accurate flow comparisons.

XL/BLT Specifications					
NPS	Nominal I.D.	Wt.	Wt. (H2O Filled)	CRR	CRR
In; mm	In; mm	Lbs/Ft; kg/m	Lbs/Ft; kg/m	Unthreaded	Threaded
1"	1.104	1.13	1.61	7.21	0.35
25	28.0	1.8	2.40	—	—
1¼"	1.452	1.46	2.25	4.63	0.17
32	36.9	2.3	3.35	—	—
1½"	1.687	1.76	2.84	4.83	0.18
40	42.8	2.8	4.23	—	—
2"	2.154	2.35	4.06	4.20	0.21
50	54.7	3.7	6.04	—	—
2½"*	2.581	4.08	6.34	TBD	TBD
65	65.5	6.05	9.45	—	—
3"*	3.200	5.01	8.49	TBD	TBD
75	81.2	7.43	12.7	—	—

* only available in XL



Project:	Sprinkler Contractor:	Date:
Engineer:	Specification Reference:	System Type:
Locations:	Comments:	



Customer Service (800) 882-5543 Fax: (800) 659-7730

• 16100 S Lathrop Ave.
Harvey, IL 60426

• 11350 Norcom Rd.
Philadelphia, PA 19154

• 2525 N 27th Ave.
Phoenix, AZ 85009

• 600 Dean Sievers Place
Morrisville, PA 19067

www.alliedtube-sprinkler.com